

PRIMER K

WATER BASED PROTECTIVE SEALER FOR TERRACOTTA FLOORS



GENERAL DESCRIPTION

PRIMER K is a water based sealer to be used with the hardner IPC for the treatment of terracotta and natural stone floors. **PRIMER K** leaves a semiglossy film that protects the surface from traffic marks, dirt pick up, absorption of stains and grease. The product is used for interior floors and in exteriors if there is not a problem of salt migration to the surface.

PRIMER K can be used in combination with the coloured paste COLOR COTTO ANTICO and COLOR COTTO MATTONE for increase particular covering colorations. When using **PRIMER K** with coloured pastes apply a first coat of neutral **PRIMER K**.

DIRECTION FOR USE

For old floors wash with DEKA P to remove oily soils and old coats of wax, and then wash with DEKACID or DETAR at 10% and then rinse with water.

In case of newly installed floors, use an acid detergent (like DEKACID at 10%-20%) to remove white efflorescences and cement residues.

Rinse well.

For better chemical resistance of the film, add the crosslinker IPC (at 1,5% ratio = 150 g of IPC per 10 kg of **PRIMER K**) before using.

Apply the first coat on a slightly damp floor to avoid levelling problems, let dry and apply a second or a third coat.

TECHNICAL DATA

Appearance	white liquid
pH	8.1 ± 0.2
Density	1.016 g/ml
Active contents	22%

WARNINGS

Keep from freezing.

Product not classified as dangerous.